



GT CTL 155 15.6" Touchcomputers (All In One)

GT 5 series commercial-grade touchcomputers (All-in-one) is available in 15.6", 21.5", 23.8", 27", and 32", elegant design with an accurate projected capacitive 10-point multitouch display with low consumption. It's an ideal touch solution for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education, and healthcare.

Features & Benefits

- Window 7, 8, 10 with Intel J1900 Processor
- Accurate PCAP Multi-touch Technology
- Full HD (1920 x 1080)
- 4GB RAM+128GB Memory
- VESA Mounting
- Edge-to-edge Design, Easy to Clean
- Anti-glare Optional
- WIFI Connector, Bluetooth optional
- USB, VGA, LAN, Multiple interfaces



Applications

- Retail
- Corporation
- Medical
- Banking
- Self-service
- Gaming
- Kiosk
- Transportation

SPECIFICATIONS

Name	15.6" Touchcomputers (All In One)	
Model	CTL155	
PC Parameters		
Processor	Intel Celeron J1900, Quad Core, 2.0GHz	
Memory	4GB	
Storage	128GB SSD	
Supported system	Windows 7/8/10 Linux	
Touch Technology	PCAP	
Touch Point	10	
LCD Panel Parameters		
Aspect Ratio	16:9	
Active Display Area (V x H)	344.16 × 193.59 mm	
Native Resolution	1920 × 1080	
Response Time (Typ.)	25ms	
Display Colors	262K	
Luminance (Typ.)	250 cd/m ²	
Contrast Ratio (Typ.)	700:1	
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10	170° (85°/85°)
	Vertical (up/down) CR≥10	170° (85°/85°)
I/O Port		
LAN	1xRJ45	
WLAN	WIFI (Optional), Bluetooth (Optional)	
USB Port	3 × USB2.0, 1 × USB3.0	
VGA/HDMI/DP (Display) Port	1 × VGA out	
Audio	1 × Line-out, 1 × Mic in	
COM Port	1 × RS232 2 × RS232(optional)	
Power In	1 × 12V DC Jet Ø 2.5	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	VESA 75 × 75 100 × 100mm	
Outline Dimension (W × H × D)	395.4 × 243.4 × 40mm	

Power Supply	External Adapter	Input Voltage : DC12V
Speaker(inside)	2×2W	
Power Consumption (type)	45W	
Operating Altitude	≤3000m	
Temperature	Operating: 0°C to 40°C, storage: -20°C to 60°C	
Humidity (non-condensing)	Operating: 20% to 80%, storage: 10% to 90%	
Agency Approvals	FCC, CE	
Warranty	2 years	

Ordering Information

Model	Part Number	Description
CTL155-RCA-0B00-A0B-1.0	110303032R	15.6", J1900, 4G+128G, 250nits, PCAP, Speaker 1×RS232
CTL155-RCA-0B00-A0B-3.0	110303083R	15.6", J1900, 4G+128G, 250nits, PCAP, Speaker 2×RS232

Optional Accessories

Model	Part Number	Description
AC cable		UK/EU/US 1500mm
Power Adapter	130102978R	50W 12V/4.17A

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., LTD reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>