

GT CTL225 21.5" Touchcomputers (All In One)

GT 5 series commercial-grade touchcomputers (All-in-one) is available in 15.6", 21.5", 23.8", 27", and 32", elegant design with an accurate projected capacitive 10-point multitouch display with low consumption. It's an ideal touch solution for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education, and healthcare.

Features & Benefits

- Window 7, 8, 10 with Intel J1900 Processor
- Accurate PCAP Multi-touch Technology
- Full HD (1920 x 1080)
- 4GB RAM+128GB SSD
- VESA Mounting
- Edge-to-edge Design, Easy to Clean
- Anti-glare Optional
- WIFI Connector, Bluetooth optional
- USB, VGA, HDMI, LAN, Multiple interfaces



Applications

- Retail
- Corporation
- Medical
- Banking
- Self-service

- Gaming
- Kiosk
- Transportation

SPE	CIE	CAT	CIO	NIC

PECIFICATIONS	21577 1 - (4117 2			
Vame	21.5" Touchcomputers (All In One)			
Model	CTL225			
PC Parameters				
Processor	Intel Celeron J1900, Quad Core, 2.0GHz			
Memory	4GB			
Storage	128GB SSD			
Supported system	Windows 7/8/10 Linux			
Touch Technology	PCAP			
Touch Point	10			
LCD Panel Parameters				
Aspect Ratio	16:9			
Active Display Area (V x H)	476.64×268.11 mm			
Native Resolution	1920×1080			
Response Time (Typ.)	18ms			
Display Colors	16.7M			
Luminance (Typ.)	250 cd/m ²			
Contrast Ratio (Typ.)	3000:1			
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 Vertical (up/down) CR≥10	178° (89°/89°) 178° (89°/89°)		
I/O Port				
LAN	1×RJ45			
WLAN	WIFI (Optional), Bluetooth (Optional)			
USB Port	3×USB2.0, 1×USB3.0			
VGA/HDMI/DP (Display) Port	$1 \times VGA$ out, $1 \times HDMI$ out			
Audio	1×Line-out, 1×Mic in			
COM Port	2× RS232(Optional)			
Power In	1×12V DC Jet ¢ 2.5			
Overall Parameters				
Case/Bezel Color	Black			
Mounting Options	VESA 75×75 100×100mm			
Outline Dimension $(W \times H \times D)$	525.6×322.2×46mm			

Power Supply	External Adapter Input Voltage : DC12V		
Webcam(inside)	Optional		
Speaker(inside)	$2 \times 2W$		
Power Consumption (type)	45W		
Operating Altitude	≤3000m		
Temperature	Operating: 0°C to 40°C, storage: -20°C to 60°C		
Humidity (non-condensing)	Operating: 20% to 80%, storage: 10% to 90%		
Agency Approvals	FCC, CE		
Warranty	2 years		

Ordering Information		
Model	Part Number	Description
CTL225-RCA-0B00-A0B-1.0	110303034R	21.5", J1900, 4G+128G, 250nits, PCAP, Speaker

Optional Accessories		
Model	Part Number	Description
AC cable		UK/EU/US 1500mm
Power Adapter	130102978R	50W 12V/4.17A