

55 Inch

Closed Frame Windows AIO

CTL557



General Touch's breed of Closed Frame Touch computer is characterized by its unified design with AL Alloy frame edges. This sleek and sturdy contraption is loaded with enticing features and options that cater to different requirements including operating on Android, Windows and Linux platforms. The Android version is equipped with a Rockchip processor, while the Windows and Linux versions utilize powerful Intel processors.

Equipped with 10-point responsive PCAP Touch, several I/O interfaces and a high resolution display, connecting and adapting to other devices and peripherals is a breeze for applications in an assortment of scenarios. Also, a Closed frame design has the standard mounting options such as floating or standalone. Hence, GT's Closed frame Touch Computers are well positioned for use in kiosks, POS systems, financial services, self-service applications and information interactive displays.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Support Windows, Linux, Android and mainstream OS
- AL Alloy frame, fashion and sturdy and durable
- General Touch PCAP technology, quality assurance
- VESA Mounting
- 43", 55" large size touch computer with OPS, support 4K solution
- Support customization and OEM/ODM
- Closed frame, compatible with various application

SPECIFICATIONS

Product Name	55 Inch Closed Frame Windows AIO	
Model	CTL557	
Motherboard Parameters		
Processor	7th Generation Intel® Core™ i5 Mobile Dual-Core CPU	
GPU	Intel® HD Graphics 620, integrated in CPU	
Memory	1 x NB-DDR4 Slot, up to 32GB	
Storage	1 x mSATA Interface, 2 x SATA Interfaces	
OS Support	Windows 7/ Windows 8/ Windows 10/ Linux (Note 1)	
Wi-Fi & Bluetooth	Mini PCI-e Module, optional (Note 2)	
4G LTE	Mini PCI-e Module, optional (Note 2)	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Display Area (W x H)	1209.6mm x 680.4mm	
Native Resolution	3840 x 2160	
Response Time (Typ.)	8ms	
Display Colors	1.07B	
Luminance (Typ.)	500nits	
Contrast Ratio (Typ.)	1200:1	
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10	178° (89°/89°)
	Vertical (Up/Down) CR≥10	178° (89°/89°)
Touchscreen Parameters		
Touch Technology	PCAP	
Touch Point	10	
Light Transmission	≥85%	
Thickness	4.5mm ± 0.3mm	

I/O Port	
LAN	1 x RJ45 (10/100/1000Mbps)
USB	2 x USB 2.0 (Type-A), 2 x USB 3.0 (Type-A)
Display	1 x VGA out, 1 x HDMI out
Audio	1 x 3.5mm Line out, 1 x 3.5mm Mic in
Antenna	2 x SMA-K, available on Wi-Fi & Bluetooth or 4G LTE model
Power	1 x AC input

Overall Parameters	
Bezel/Case Colour	Black
Mounting Options	VESA 200mm x 400mm
Outline Dimensions	1259.4mm x 736.4mm x 72.8mm (W x H x D)
Input Voltage Range	110V-240V AC
Speaker	2 x 5W Built-in, optional
Power Consumption	TBD
Operating Altitude	≤3000m
Temperature	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non-condensing)	Operating: 20% to 80%, storage: 10% to 90%
Carton Dimensions	TBD
Weight	TBD
MTBF	50,000 Hours Demonstrated
Agency Approvals	TBD
Warranty	2 years

Note 1: The default operating system is Windows 10 IoT Enterprise x64, and Microsoft® Product Key is an optional accessory.

Note 2: There is only 1 Mini PCI-e slot for Wi-Fi & BT 2-in-1 module or 4G LTE module installation.

Ordering Information

Part Name	Part Number	Description
CTL557-RCS-2B00-C0D-1.0	10302020040R	8GB RAM, 128GB mSATA SSD, 2 x 5W Built-in Speakers, Wi-Fi&BT 2 in 1 Module

Optional Accessories

Part Name	Part Number	Description
Microsoft® Product Key	30208180003R	Windows 10 IoT Enterprise (OEM)
US Power Cable	30301010010R	1.5m
EU Power Cable	30301010011R	1.5m
UK Power Cable	30301010018R	1.5m

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>