



GT OBL155

15.6" Closed Frame Touchmonitor

With a compact form factor design, the General Touch 15.6" OBL155 monitor offers the flexibility to install as a cashier POS terminal, a customer-facing point of sale, self-service kiosk, signage or hospitality applications. It provides two USB Type-C, one Mini HDMI and one headset ports. One USB-C single cable can simultaneously connect power, touch data, audio and video streams. By reducing the number of cables required for any setup from 4 to 1, installation and servicing is a breeze. In case the PC isn't equipped with USB-C yet, you can still use traditional Mini HDMI to connect to the PC while powering the monitor with a single USB-C cable.


Efforts of sorting through an unexpected mess of exposed cables which are both ugly and often a source of instability. The greatness of USB-C connectivity relies on its versatility, since it's capable of simultaneously transmission of computer data, video and audio streaming, even power via a single cable.

Features & Benefits

- Accurate PCAP Multitouch Technology
- Sleek Appearance
- Optical bonding
- External VESA Mounting
- Easy Integration and Low Maintenance
- 2×USB-C, Mini HDMI
- Optional Anti-glare

Applications

- POS
- Gaming
- Medical
- Self-service
- Corporation
- Kiosk
- Banking
- Transportation



Single USB-C cable to transmit video, audio, touch and power

SPECIFICATIONS

Name	15.6" Closed Frame Touchmonitor	
Model	OBL155	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Display Ratio	16:9	
Active Display Area	344.16mm × 193.59mm	
Native Resolution	1920×1080@60Hz	
Response Time(Typ.)	25ms	
Display Colors	16.7M	
Luminance (Typ.)	350nits	
Contrast Ratio (Typ.)	1000:1	
Viewing Angle(Typ.)	Horizontal(left/right) CR≥10	170°(85°/85°)
	Vertical(up/down) CR≥10	170°(85°/85°)
Touch Screen Parameters		
Touch Technology	Projected Capacitive Touch (PCAP)	
Surface Treatment	Strengthened, Anti-glare	
Active Area(W x H)	345.2×194.5mm±0.3mm	
Thickness(Total)	2.4±0.3mm	
Light Transmission	≥83%	
Response Time	8-10ms	
Touch Screen Interface	USB-C	
Touch Point	10	
Overall Parameters		
Case/Bezel Color	Silver middle frame with black back cover	
Mounting Options	VESA : 75×75mm	
Outline Dimensions (W×H×D)	395.4×245.4×27.6mm	
Power Supply	USB-C (5~20V DC)	
On Screen Display (OSD)	Control(back): Power, Auto, Up, Down, Menu	
Power Consumption(Typ.)	9.8W	
Speaker	2×0.7W	
Webcam	NA	

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0 °C to 40°C, storage: -20°C to 60 °C
Humidity (Non Condensing)	Operating: 20%-80%, storage: 10%-90%
I/O	2×USB-C, Mini HDMI, Audio Out
Accessories	USB-C Cable× 1, 3000mm
Carton Box Dimensions (4 units in box a carton)	480mm×390mm×390mm
Weight (4 units in box a carton)	Net: 3.2kg Gross: 15.8kg
MTBF	30,000 hours demonstrated
Agency Approvals	CE, FCC, CCC
Warranty	3 years

Ordering Information

Model	Part Number	Description
OBL155-RC3CA0-UT320S-1.0	110303341R	15.6", 16:9, 350nits, PCAP, 2*USB-C, Anti-glare

Contact sales for other options

Optional Accessories

Model	Part Number	Description
NA		

Go to www.generaltouch.com for more products and information, or contact us.
 General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120
 Fax: 0086-28-85124115
 E-mail: info@generaltouch.com
<http://www.generaltouch.com>