



GT OML24D 23.8 Inch LED-Framed Double-Sided Monitor

23.8" lightweight and slim double-sided monitor for table gaming applications.

Features & Benefits

- Double-Sided Display
- Industrial-grade PCB-mounted LEDs
- RGB/Addressable Modes
- Edge-to-Edge Design, True Flat, Easy to Clean
- Pole, Base and Electronic Box Design for Easy Installation





Applications

■ Table Gaming



SPECIFICATIONS

Name	23.8 Inch LED-Framed Double-Sided Monitor	
Model	OML24D-R02000-0D2F40-2.0	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Aspect Ratio	16:9	
Active Area (W x H)	527.04 × 296.46 mm	
Native Resolution	1920 × 1080 @ 60 Hz	
Response Time (Typ.)	14 ms	
Display Colors	16.7 M	
Luminance (Typ.)	250 nits	
Contrast Ratio (Typ.)	1000:1	
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89° Vertical (up/down) CR≥10 89°/89°	
Screen Parameters		
Surface Treatment	Tempered or Chemically Strengthened	
Thickness (Total)	2.0 mm	
Light Transmission	≥ 90%	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	Pole + Quick Mount Base, portrait mode	
Outline Dimensions (W \times H \times D)	918.5 mm × 350.1 mm× 40.0 mm	
Power Supply	Input Voltage Range: +12 VDC ± 5%	
On Screen Display (OSD)	Control (remote): Power, Auto, Up, Down, Menu	
Power Consumption (Max.)	90 W	
0 1 1111 1	≤ 3000 m	
Operating Altitude	_ 5000 111	



Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C		
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%		
I/O	HDMI, HDMI, DP, USB (Type B)		
Accessories	Optional		
Carton Box Dimensions (1 unit in one carton)	780 mm (L) \times 470 mm (W) \times 240 mm (H)		
Weight	Net: 11 kg Gross: 18.5 kg		
MTBF	50,000 hours demonstrated		
LED Lights Color	Multicolor		
LED Lights Location	4 LED lights bar (Front & Edge)		
LED Controller	Built-in		
Agency Approvals	CE, FCC		
Warranty	3 years		

Ordering Information			
Model	Part Number	Description	
OML24D-R02000-0D2F40- 2.0		23.8", 16:9, 250 nits, non-touch, LED-framed double-sided monitor, LED lights location front & edge, portrait mode	

Optional Accessories		
Model	Part Number	Description
USB Cable	130300224R	1500mm, male to male
HDMI Cable	130300881R	1500mm, male to male
DP Cable	130300932R	1500mm, male to male
Adaptor	130104010R	Power Adapter 12 V/90 W/2.5 mm/1200 mm
Power Cable		1500 mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

http://www.generaltouch.com