


27 Inch

LED-Framed Monitor

OML27H




The LED-Framed monitor dazzles with ambient lighting effects on the front and/or back of its sides. The color, style, and rhythm of the lights can be used as adornments, alerts, attractions, flags, indicators or fanfare that will surely boost the interactive functions of a display for both the users and operators.

To match different design styles, General Touch offers various LED light strip designs, including Front design with LED lights visible from the front, Edge design and Halo design with LED lights visible from the front and sides. The rear of the LED-Framed monitor has multiple design options too, such as rear-fire LED strips on four sides, U-shaped strips on three sides, or two parallel strips on the short or long edges. These combinations offer a wide variety of style and luster.

The GT LED-Framed monitor stands out with their exceptional lighting effects, featuring no hot spots, dark spots, and dark corners, and ensuring a high level of uniformity with finely crafted, well-sealed, and free from LED light leakage. To facilitate customer control over the LEDs, GT provides protocols and controllers for customers to choose from. The LED controllers can be embedded or external, and it also supports customer-supplied controllers. The lighting effects offer dozens of standard modes and can be customized to meet specific customer requirements.

LED-Framed monitors have been widely used in various scenes and domains, including gaming, kiosks, entertainment, EV chargers, meetings, and way-finding. The landscape, portrait, and VESA mounting options allow for quick and convenient integration with different environments, fulfilling customers' demands for high-quality dual interaction experiences.



Gaming

Kiosk

Vending Machine

- LED-Framed, Mini-Halo design
- No hot spot, dark spot, dark corner, high level uniformity
- Metal frame, precisely and finely crafted
- Well sealed, non LED light leakage
- True flat, closed frame, compatible with various application

SPECIFICATIONS

Product Name	27 Inch LED-Framed Monitor
Model	OML27H
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	597.89mm × 336.31mm
Native Resolution	1920 × 1080 @ 60Hz
Response Time (Typ.)	14ms
Display Colors	16.7M
Luminance (Typ.)	300nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal: CR≥10 89°/89° Vertical: CR≥10 89°/89°
Screen Parameters	
Surface Treatment	Tempered, Optional: Anti-Glare
Thickness (Total)	3.0mm
Light Transmission	≥ 90%
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 75mm × 75mm, 100mm × 100mm, 400mm × 150mm
Outline Dimensions (W×H×D)	637.0mm × 380.8mm × 52.2mm
Power Supply	Input Voltage Range: Monitor: +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter RGB LED Lights: +7VDC~+40VDC, mating Molex 43025-0600 Optional LED controller (External): +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	30W (Monitor without RGB LED Lights) 25W (RGB LED Lights)
Operating Altitude	≤ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	HDMI, DP
Accessories	Optional
Carton Box Dimensions	784mm (L) × 275mm (W) × 533mm (H), 2 units in one carton
Weight	Net: 8.5kg, Gross: 20.5kg
MTBF	50,000 hours demonstrated

LED Lights Color	Multicolor
LED Lights Location	4 LED lights bar (Mini-Halo)
LED Controller (External)	Optional
Agency Approvals	CE, FCC, UKCA, UL
Warranty	3 years

Ordering Information

Model	Part Number	Description
OML27H-L03000-0D3F40-1.0	10205010103L	27", FHD, 16:9, 300nits, non-touch, HDMI/DP, 4 LED lights bar (Mini-Halo)

Optional Accessories

Model	Part Number	Description
HDMI Cable	30302030001R	HDMI Cable A Male-A Male 1500mm
DP Cable	30302010001R	DP Cable Male-Male 1500mm
LED Controller Kit	20701040010R	12V / 50W Addressable LED Controller Kit
Adapter	30207010005R	Power Adapter 12V / 50W / 2.5mm / 1500mm
Power Cable	30301010018R	UK
	30301010011R	EU
	30301010010R	US

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com