



GT OTJ555 55 Inch Curved Touchmonitor (J-type)

With J Type format, 4K UHD, GT Curved Touch Monitors, allow for more impressive visual contents and captivating play. Sleek appearance, engaging visuals and accurate PCAP multi-touch experience let excited players immerse into the gaming atmosphere and enjoyment. It's an ideal touch solution widely used in the gaming, casino and sports betting.

Features & Benefits

- Unique Industrial-grade Design
- Curved 1500R Comfortable Viewing Experience
- Accurate PCAP Multi-touch Technology
- 4K Resolution
- External VESA Mounting, Portrait or Landscape
- Edge-to-edge Design, Easy to Clean
- Customization Possible





Applications

Gaming

■ SLOT

Casino



SPECIFICATIONS

Name	55 Inch Curved Touchmonitor (J-type)		
Model	OTJ555-RC5000-UD5400-2.0		
LCD Panel Parameters			
Display Technology	Active Matrix TFT-LCD With LED Backlight		
Aspect Ratio	16:9		
Active Area (W x H)	1209.6mm×680.4mm		
Native Resolution	3840×2160@60Hz		
Response Time (Typ.)	8ms		
Display Colors	1.07B		
Luminance (Typ.)	500nits		
Contrast Ratio (Typ.)	4000:1		
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89° Vertical (up/down) CR≥10 89°/89°		
Touch Screen Parameters			
Touch Technology	Projected Capacitive (PCAP)		
Surface Treatment	Tempered or Chemically Strengthened		
Thickness (Total)	4.5 ± 0.5 mm		
Light Transmission	≥83%		
Response Time (Typ.)	10ms		
Touch Screen Interface	USB		
Touch Point	10		
Overall Parameters			
Case/Bezel Color	Black		
Radius	1500R		
Mounting Options	VESA: 600mm×400 mm		
Outline Dimensions $(W \times H \times D)$	1261.8mm × 732.0mm× 196.0mm		
Power Supply	Input Voltage Range: +24VDC ± 5%		
On Screen Display (OSD)	Control (remote): Power, Auto, Up, Down, Menu		
Power Consumption (Max.)	150W		
Operating Altitude	≤3000m		
System Support	Windows 7 or later, Linux 4.4 or later		



Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C		
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%		
I/O	HDMI, DVI, DP, USB (Type B)		
Accessories	Optional		
Carton Box Dimensions (1 unit in one carton)	TBD mm (L) \times TBD mm (W) \times TBD mm (H)		
Weight	Net: TBD Gross: TBD		
MTBF	50,000 hours demonstrated		
Agency Approvals	CE, FCC		
Warranty (Default)	1 year		

Ordering Information				
Model	Part Number	Description		
OTJ555-RC5000-UD5400-2.0		55" "J type", 1500R, 4K, 16:9, 500nits, PCAP, USB, HDMI/DVI/DP		

Contact sales for other options

Optional Accessories		
Model	Part Number	Description
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)- Output :24(VDC)-6.25A-150W-4PIN
Power Cable		1500mm
USB Cable	130300224R	1500mm, male to male
DVI Cable	130300720R	1500mm, male to male
HDMI Cable	130300881R	1500mm, male to male
DP Cable	130300932R	1500mm, male to male

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

http://www.generaltouch.com