



Premium Product


- >Multi-touch
- >Precision Engineering
- >Eye-Catching

10 Inch Closed Frame Touch Monitor

OTL105 is a touchmonitor using industrial grade LED, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or monitor, the OTL105 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education and healthcare.

Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

SPECIFICATIONS

Name	10 Inch Closed Frame Touch Monitor
Model	OTL105-RC3000-UC4A00-1.0
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:10
Active Area (W x H)	216.96×135.60mm
Native Resolution	1280×800@60Hz
Response Time (Typ.)	30ms
Display Colors	16.2million
Luminance (Typ.)	400nits; with P-Cap 340nits
Contrast Ratio (Typ.)	900:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 85°/85° Vertical (up/down) CR≥10 85°/85°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Tempered Strengthened Optional: Anti-Glare
Active Area(W x H)	217.6×136.2±0.3mm
Thickness(Total)	2.75±0.2mm
Light Transmission	≥83%
Response Time	8ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Silver Middle Frame With Black Back Cover
Mounting Options	VESA: 75×75 mm
Outline Dimensions (W×H×D)	261.3mm × 179.3mm × 42.8mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz Input Voltage Range: +12VDC ± 5%, DC Jet ∅ 2.5mm
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 15W
Speaker	Optional
Webcam	NA

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, DVI, USB (Type B)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions	426mm (L) × 355mm (W) × 158mm (H)
Weight	Gross: 3.8kg Net: 5.4kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE , FCC
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL105-RC3000-UC4A00-1.0	110303761R	10", 16:10, 400nits, P-Cap, USB, VGA & DVI, Black

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adaptor	130102978R	12V/4.17A, DC Cable: 1500mm, DC Jet ∅ 2.5mm
DVI Cord	130300720R	1500mm
	130300338R	UK
Power Cord	130300339R	EU 1500mm
	130300340R	US

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>