



GT OTL19S 19" Open Frame Touchmonitor with a Stylus

GT OTL19S is an 19" touchmonitor with projected capacitive 10-point multitouch technology with remarkable clarity and vivid color, which brings you better touch experience. With an electromagnetic pen, OTL19S offers more accurate and natural pen strokes. The OTL19S industrial-grade high performance and professional design is better suited for applications such as education, banking and medical.

Features & Benefits

- Accurate PCAP Multitouch Technology
- Electromagnetic Pen
- Sleek Appearance
- Anti-scratch Touchscreen
- VESA Mounting
- Easy Integration and Low Maintenance
- VGA, DVI Interface
- Commercial-grade Continuous (24/7) Use
- Optional Anti-glare
- 3 Years Warranty



Applications

- Education
- Corporation
- Medical
- Banking

SPECIFICATIONS

Name	19" Open Frame Touchmonitor with a Stylus	
Model	OTL19S	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD with LED Backlight	
Display Ratio	5:4	
Active Display Area	376.32mm × 301.06mm	
Optimum resolution	1280 × 1024 @ 60 Hz	
Response Time(Typ.)	5 ms	
Display Colors	16.7 million	
Luminance (Typ.)	250 cd/m ²	
Contrast Ratio (Typ.)	1000:1	
Viewing Angle(Typ.)	Horizontal(left/right) CR≥10	170° (85° /85°)
	Vertical(up/down) CR≥10	160° (80° /80°)
Touch Screen Parameters		
Touch Technology	Projected Capacitive Touch (PCAP)	
Surface Treatment	Tempered	
	Anti-glare (Optional)	
Thickness(Total)	2.4±0.2mm	
Light Transmission	88%±3%	
Response Time	≤8ms	
Touch Screen Interface	USB 2.0	
Touch Point	10	
Electromagnetic Parameters		
Electromagnetic technology	Passive electromagnetic handwriting technology, including a stylus	
Pressure rating	2048	
Report Rate	≥138PPS	
Data encryption	Hardware encryption (Optional)	
Communication interface with host	USB 2.0 (HID)	
Overall Parameters		
Case/Bezel Color	Screen body printing black, the rest is silver	
Mounting Options	VESA : 75×75mm & 100×100mm, Side Mounting	
Outline Dimensions (W×H×D)	432.80mm× 360.20mm× 46.8mm	

SPECIFICATIONS

Power Supply	Input Voltage Range: +12VDC \pm 5%
Power Consumption	Control(back): Power, Auto, Up, Down, Menu
Operating System	Windows 7/8/8.1/10, Android 4.0 and above, Linux (kernel version 3.5 and above)
Operating Altitude	\leq 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, DVI, USB-B
Accessories	Cables: VGA \times 1, USB \times 1, 1.5m Length
Carton Box Dimensions (3 units in 1 carton)	515.00mm \times 318.00mm \times 490.00mm
Weight	Net: 5.24 kg
	Gross: 17.62 kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE, FCC
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL19S-RD3F00-UC31LE-1.0	110302992R	19", 300nits, PCAP, Electromagnetic handwriting, encryption

Optional Accessories

Model	Part Number	Description
Adaptor	130102978R	12V/4.17A, DC Cable: 1500mm, DC Jet \varnothing 2.5mm
	130300338R	UK 1500mm
Power Cord	130300339R	EU 1500mm
	130300340R	US 1500mm
DVI Cord	130300720R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>