

55 Inch

Closed Frame Touchmonitor

OTL555



General Touch has developed a wide range of closed frame touchmonitors with FHD/4K resolutions and sizes from 10.1 to 55 inches. Catering to those who seek premium touch solutions with top-tier displays, its standard closed frame design offers flexibility with standalone or floating-mount options on top of the usual variety of other installation preferences. The above 3mm robust cover glass has undergone rigorous testing, complying with IK08 ball-drop requirements to ensure durability when deployed in public environments. With useful features including analog and digital interfaces, and multi-lingual, this touchmonitor offers users a comprehensive and user-friendly experience.

Industrial-grade components are used to ensure long-term product viability and availability. The physical structure utilizes various materials such as aluminum, sheet metal, and plastic that consummates into a sound, enduring and stylish construct. Designed with touch functionality at its core, GT's masterful innovation and production expertise guarantees a well-integrated contraption with energy saving and lower heat generation. The result is a solid and energy-efficient touchmonitor with sleek contours that will complement well with the latest kiosk designs for retail, self-service, gaming, transportation, and other commercial applications.



Gaming



Kiosk



Vending Machine



Industrial Automation

- Closed frame, with Industry quality and long lifespan
- General Touch PCAP technology, quality assurance
- 4K resolution for large size and others FHD or HD
- Full range size from 10.1 inch to 55 inch, one stop for you
- Industrial-grade raw materials, better for industry
- VESA mounting
- IK08 impact resistance

## SPECIFICATIONS

Name	55 Inch Closed Frame Touchmonitor
Model	OTL555
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	1209.6mm × 680.4mm
Native Resolution	3840×2160@60Hz
Response Time (Typ.)	8ms
Display Colors	1.07G
Luminance (Typ.)	500nits, with PCAP 415nits
Contrast Ratio (Typ.)	3000:1
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10 89°/89° Vertical (Up/Down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	PCAP
Surface Treatment	Strengthened Optional: Anti-Glare
Active Area(W x H)	1211.6mm × 682.4mm ±0.5mm
Thickness(Total)	4.38mm ±0.3mm
Light Transmission	≥83%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Silver middle frame with black back cover
Mounting Options	VESA: 400mm × 400mm
Outline Dimensions (W×H×D)	1259.4mm × 736.4mm × 71.3mm
Power Supply	Input Voltage Range: 100-240V AC, 50-60 HZ
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 186W
Speaker	Optional

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, Storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%
I/O	DVI, HDMI, DP, USB (Type B, For Touch)
Accessories	Cables: USB×1, 1.5m Length
Carton Box Dimensions	1390mm (L) × 190mm (W) × 850mm (H), 1 units in one carton
Weight	Net: 35.18kg, Gross: 40.28kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE, FCC
Warranty	3 years

### Ordering Information

Model	Part Number	Description
OTL555-RC5000-UD8U00-2.0	10202010591R	55", 16:9, 4K, 500nits, PCAP, USB, DVI & HDMI & DP, Black

Contact sales for other options

### Optional Accessories

Model	Part Number	Description
DVI Cable	30302020002R	1500mm
	30301010018R	UK
Power Cable	30301010011R	EU
	30301010010R	US
HDMI Cable	30302030001R	1500mm
DP Cable	30302010001R	1500mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>