

10.1 Inch

Rear Mount Touchmonitor

RTL106





Jam-packed with advanced technical features, the latest General Touch Rear Mount Touchmonitor has been engineered to meet demanding operating environments without compromising its aesthetic appeal. Crafted with industrial-grade materials and precision molding, one could tell it could worth its weight in gold just by looking and handling it.

At its heart, an EETI chip drives its PCAP touch functions, coupled with an edge-to-edge cover glass that attains IP65 rating (Front surface) and easily survives the IK07 ball-drop test. This tough nut performs even in diverse and hostile environments. No wonder, not all PCAP touchscreens are created the same. In certain sizes, the PCAP touchscreen is optically bonded to its industrial grade LCD panel that spells unparalleled motion imagery in its class that is lifelike and immersive for any users.

Other desirable physical features include svelte profile, both DP and HDMI interfaces, external OSD menu control and versatile mounting options with adjustable brackets provided. Backed by GT's 3-year warranty, this Rear Mount PCAP Touchmonitor is pleasing to the eye, potent to work with and pleasurable to operate. With sizes ranging from 10.1 to 43 inches, GT's Rear Mount Touchmonitors can be proudly deployed in sectors like Retail, Entertainment, Financial Equipment, Self-service Kiosk, Lottery, Transport, Industrial Automation and more.



- Flexible installation choices and adjustable mounting brackets render the equipment seamlessly compatible
- The hardware modular design embodies a sleek and integrated aesthetic, exuding a sense of fashionable sophistication
- Front-facing, it achieves the esteemed IP65 rating
- Externally tethered OSD facilitates remote image adjustments

- Three-year warranty
- A comprehensive range of 10.1 to 43 inches, facilitating all-in-one procurement
- In-house production of exceptional touchscreens, suitable for a myriad of industries
- Certain sizes offer the option of optical bonding technology, providing a more authentic display



SPECIFICATIONS

Product Name	10.1 Inch Rear Mount Touchmonitor		
Model	RTL106		
LCD Panel Parameters			
Display Technology	Active Matrix TFT-LCD With LED Backlight		
Aspect Ratio	16:10		
Active Area (W x H)	216.96mm × 135.60mm		
Native Resolution	1280 × 800@60Hz		
Response Time (Typ.)	25ms		
Display Colors	262K		
Luminance (Typ.)	500nits, with PCAP 425nits		
Contrast Ratio (Typ.)	1300:1		
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 85°/85°		
	Vertical (up/down) CR≥10 85°/85°		
Touch Screen Parameters			
Touch Technology	PCAP		
Surface Treatment	Strengthened Ontional Anti Clare		
Active Area(My H)	Optional: Anti-Glare 217.80mm × 136.40mm±0.3mm		
Active Area(W x H)	3.3mm±0.3mm		
Thickness(Total)	≥85%		
Light Transmission	10ms		
Response Time	USB		
Touch Screen Interface Touch Point	10		
Overall Parameters	Displa		
Case/Bezel Color	Black VECA 75 man v 75 man Boar Mayorting Cida Mayorting		
Mounting Options	VESA: 75mm × 75 mm, Rear Mounting, Side Mounting		
Outline Dimensions (W×H×D)	255.8mm × 178.5mm × 36.9mm		
Power Supply	Input Voltage Range: +12V DC ± 5%, Coaxial power jack 2.1mm pin outer		
	diameter		
On Screen Display (OSD)	Control (External): Power, Auto, Up, Down, Menu		
Power Consumption	MAX: 15W		
Speaker	NA		
Webcam	NA		



Operating Altitude	≤3000m		
Temperature Range	Operating: 0°C to 50°C, Storage: -20°C to 60°C		
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%		
I/O	VGA, HDMI, DP, USB (Type B), Mini DIN (External OSD)		
Accessories	Cables: VGA×1, USB×1, 1.5m Length, External OSD		
Carton Box Dimensions	370mm (L) × 340mm (W) × 355mm (H), 4 units in one carton		
Weight	Net: 2.42kg, Gross: 13.62kg		
MTBF	50,000 hours demonstrated		
Agency Approvals	CE, FCC		
Warranty	3 years		

Ordering Information	g Information			
Model	Part Number	Description		
RTL106-RC4000-UD5A00-1.0	10202010326R	10.1", 16:10, 500nits, PCAP, USB, VGA & HDMI & DP, Black		

Contact sales for other options

Optional Accessories			
Model	Part Number	Description	
Adapter	30207010011R	12V/5A, DC Cable: 1200mm, DC barrel plug 2.1mm pin inner diameter	
	30301010018R	UK	
Power Cable	30301010011R	EU 1500mm	
	30301010010R	US	
HDMI Cable	30302030001R	1500mm	
DP Cable	30302010001R	1500mm	
Brackets	20703000028R	See The Drawing	

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

http://www.generaltouch.com