


15 Inch

Rear Mount SAW Touchmonitor

RTL153



The General Touch Rear Mount Surface Acoustic Wave (SAW) Touchmonitor with CCC, CE and FCC certifications is a low-cost and durable touch solution. Its extended lifecycle is evidenced from years of continued field operations beyond its warranty period. The SAW touchscreens produced by General Touch are protected by international and domestic patents, and they offer accurate touches, drift-free operation, and low power consumption, with anti-glare as an option.

With flexible installation options and adjustable mounting brackets, it can be seamlessly integrated into existing systems or equipments. Available in sizes ranging from 15 to 32 inches, these no frills SAW touchmonitors are a practical choice for various public applications, including self-service terminals, financial instruments, rail transit, industrial control, and interactive digital signage.



Kiosk



Vending Machine



Industrial Automation

- In-house SAW touch technology, meet rich customization requirements
- Vandal-proof or Anti-glare optional, adapt to complex environments
- Flexible installation options and adjustable mounting brackets, easy integration and low maintenance
- Low power consumption
- Comply with CCC, CE and FCC certifications
- Available in a range of sizes from 15 to 32 inches
- A 3-year warranty guarantees an enduring lifecycle

SPECIFICATIONS

| | |
|--------------------------------|--|
| Product Name | 15 Inch Rear Mount SAW Touchmonitor |
| Model | RTL153 |
| LCD Panel Parameters | |
| Display Technology | Active Matrix TFT-LCD with LED Backlight |
| Aspect Ratio | 304.128mm × 228.096mm |
| Active Area (W x H) | 1024 × 768 |
| Native Resolution | 23ms |
| Response Time (Typ.) | 16.2 million |
| Display Colors | 350nits; with SAW 315nits |
| Luminance (Typ.) | 2500:1 |
| Contrast Ratio (Typ.) | Horizontal (left/right) CR≥10 88° /88° |
| Viewing Angle (Typ.) | Vertical (up/down) CR≥10 88° /88° |
| | 304.128mm × 228.096mm |
| Touch Screen Parameters | |
| Touch Technology | SAW |
| Surface Treatment | Optional: Anti-glare |
| Active Area | 304.40mm × 228.40mm |
| Thickness(Total) | 6.00 ± 0.2mm |
| Light Transmission | ≥90% |
| Response Time | 10.4ms |
| Touch Screen Interface | USB / RS232 |
| Touch Point | 1 |
| Overall Parameters | |
| Case/Bezel Color | Gray |
| Mounting Options | Side Mounting, VESA: 75 × 75mm, 100 × 100mm |
| Outline Dimensions (W × H × D) | 336.0mm × 264.0mm × 43.8mm |
| Power Supply | Input Voltage Range: +12V DC ± 5%, Coaxial power jack 2.5mm pin outer diameter |
| On Screen Display (OSD) | Control (back): Power, Auto, Up, Down, Menu |
| Power Consumption | MAX: 25W |
| Operating Altitude | ≤3000m |

| | |
|---|--|
| Temperature Range | Operating: 0°C to 40°C, storage: -20°C to 60°C |
| Humidity (Non Condensing) | Operating: 20% to 80%, storage: 10% to 90% |
| I/O | VGA, USB (Type B) , RS232 |
| Accessories | Cables: VGA×1, USB×1, 1.5m Length |
| Carton Box Dimensions (1 unit in one carton) | 360mm × 330mm × 335mm |
| Weight | Gross: 6kg, Net: 4.5kg |
| MTBF | 50,000 hours demonstrated |
| Agency Approvals | CCC, CE , FCC |
| Warranty | 3 years |

Ordering Information

| Model | Part Number | Description |
|----------------|--------------|--|
| RTL153-R06-SUD | 10201010003R | 15", 4:3, 350nits, SAW, USB & RS232, VGA |

Optional Accessories

| Model | Part Number | Description |
|---------------|--------------|------------------------------------|
| RS232 Cable | 30302060007R | RS232 Cable CCS175A-APT12 |
| Power Adapter | 30207010005R | Power Adapter 12V/50W/2.5mm/1500mm |
| Power Cord | 30301010010R | US |
| | 30301010011R | EU 1500mm |
| | 30301010018R | UK |

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>