

## 21.5 Inch Open Frame Touch Monitor



RTL226 is a LED industrial Touchmonitor, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the RTL226 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

### Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



### Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

## SPECIFICATIONS

Name	21.5 Inch Open Frame Touch Monitor
Model	RTL226
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	476.64×268.11mm
Native Resolution	1920×1080@60Hz
Response Time (Typ.)	18ms
Display Colors	16.7million
Luminance (Typ.)	250nits; with P-Cap 225nits
Contrast Ratio (Typ.)	3000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened
	Optional: Anti-Glare
Active Area(W x H)	476.4×268.1±0.3mm
Thickness(Total)	3.3±0.3mm
Light Transmission	≥85%
Response Time	8~10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 100×100 mm; Rear Mounting; Side Mounting
Outline Dimensions (W×H×D)	516mm × 311mm × 37.9mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz
	Input Voltage Range: +12VDC ± 5%, Jet Ø2.1mm
On Screen Display (OSD)	Control (External): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 20W
Speaker	NA
Webcam	NA

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 50°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, DP, USB (Type B), Mini Din(External OSD)
Accessories	Cables: VGA×1, USB×1, 1.5m Length; Bracket×2; OSD Remote
Carton Box Dimensions (2 units in one carton)	630mm (L) × 250mm (W) × 430mm (H)
Weight	Net: 5.56kg Gross: 14.62kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE , FCC, UL
Warranty	3 years

#### Ordering Information

Model	Part Number	Description
RTL226-LRPCZ04-UHPDA	110302573L	21.5", 16:9, 250nits, P-Cap, USB, VGA & HDMI & DP, Black
RTL226-LRPCZ04A-UHPDA		21.5", 16:9, 250nits, P-Cap, USB, VGA & HDMI & DP, Black Anti-Glare

Contact sales for other options

#### Optional Accessories

Model	Part Number	Description
Adaptor	130104158R	12V/5A, DC Cable: 1200mm, DC Jet ø2.1mm
	130300338R	UK
Power Cord	130300339R	EU 1500mm
	130300340R	US
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>