

21.5 Inch

Rear Mount Touchmonitor

RTL226





Jam-packed with advanced technical features, the latest General Touch Rear Mount Touchmonitor has been engineered to meet demanding operating environments without compromising its aesthetic appeal. Crafted with industrial-grade materials and precision molding, one could tell it could worth its weight in gold just by looking and handling it.

At its heart, an EETI chip drives its PCAP touch functions, coupled with an edge-to-edge cover glass that attains IP65 rating (Front surface) and easily survives the IK07 ball-drop test. This tough nut performs even in diverse and hostile environments. No wonder, not all PCAP touchscreens are created the same. In certain sizes, the PCAP touchscreen is optically bonded to its industrial grade LCD panel that spells unparalleled motion imagery in its class that is lifelike and immersive for any users.

Other desirable physical features include svelte profile, both DP and HDMI interfaces, external OSD menu control and versatile mounting options with adjustable brackets provided. Backed by GT's 3-year warranty, this Rear Mount PCAP Touchmonitor is pleasing to the eye, potent to work with and pleasurable to operate. With sizes ranging from 10.1 to 43 inches, GT's Rear Mount Touchmonitors can be proudly deployed in sectors like Retail, Entertainment, Financial Equipment, Self-service Kiosk, Lottery, Transport, Industrial Automation and more.



- Flexible installation choices and adjustable mounting brackets render the equipment seamlessly compatible
- The hardware modular design embodies a sleek and integrated aesthetic, exuding a sense of fashionable sophistication
- Front-facing, it achieves the esteemed IP65 rating
- Externally tethered OSD facilitates remote image adjustments

- Three-year warranty
- A comprehensive range of 10.1 to 43 inches, facilitating all-in-one procurement
- In-house production of exceptional touchscreens, suitable for a myriad of industries
- Certain sizes offer the option of optical bonding technology, providing a more authentic display



SPECIFICATIONS

Product Name	21.5 Inch Rear Mount Touchmonitor		
Model			
LCD Panel Parameters	RTL226		
	Active Matrix TET LCD With LED Booklight		
Display Technology	Active Matrix TFT-LCD With LED Backlight		
Aspect Ratio	16:9 476.64mm × 268.11mm 1920×1080@60Hz		
Active Area (W x H)			
Native Resolution			
Response Time (Typ.)	18ms		
Display Colors	16.7million		
Luminance (Typ.)	250nits, with PCAP 225nits		
Contrast Ratio (Typ.)	3000:1		
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°		
	Vertical (up/down) CR≥10 89°/89°		
Touch Screen Parameters			
Touch Technology	PCAP		
Surface Treatment	Strengthened Class		
A (' A ()A/ LI)	Optional: Anti-Glare 476.4mm × 268.1mm±0.3mm		
Active Area(W x H)			
Thickness(Total)	3.3mm±0.3mm		
Light Transmission	≥85%		
Response Time	10ms		
Touch Screen Interface	USB		
Touch Point	10		
Overall Parameters			
Case/Bezel Color	Black		
Mounting Options	VESA: 100mm ×100 mm, Rear Mounting, Side Mounting		
Outline Dimensions (W×H×D)	516mm × 311mm × 37.9mm		
Power Supply	Input Voltage Range: +12V DC ± 5%, Coaxial power jack 2.1mm pin outer		
On Screen Display (OSD)	diameter Control (External): Power, Auto, Up, Down, Menu		
	MAX: 20W		
Power Consumption	NA NA		
Speaker			
Webcam	NA		



Operating Altitude	≤3000m		
Temperature Range	Operating: 0°C to 50°C, Storage: -20°C to 60°C		
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%		
I/O	VGA, HDMI, DP, USB (Type B), Mini DIN (External OSD)		
Accessories	Cables: VGA×1, USB×1, 1.5m Length, Bracket×2, External OSD		
Carton Box Dimensions	630mm (L) × 250mm (W) × 430mm (H), 2 units in one carton		
Weight	Net: 5.56kg, Gross: 14.62kg		
MTBF	50,000 hours demonstrated		
Agency Approvals	CCC, CE, FCC, UL		
Warranty	3 years		

Ordering Information					
Model	Part Number	Description			
RTL226-LRPCZ04-UHPDA	10202010091L	21.5", 16:9, 250nits, PCAP, USB, VGA & HDMI & DP, Black			

Contact sales for other options

Optional Accessories	tional Accessories						
Model	Part Number	Description	n				
Adapter	30207010011R		Cable: 1200mm, DC barrel plug ner diameter				
	30301010018R	UK					
Power Cable	30301010011R	EU	1500mm				
	30301010010R	US					
HDMI Cable	30302030001R		1500mm				
DP Cable	30302010001R		1500mm				

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120
Fax: 0086-28-85124115
E-mail: info@generaltouch.com
http://www.generaltouch.com